


TRAVI HE

UNI 5397

- (*) A = serie leggera
 B = serie normale
 M = serie rinforzata



designazione abbreviata (*)	sezione cm ²	dimensioni						caratteristiche riferite asse neutro x - x Y - Y			
		h mm	b mm	a mm	e mm	r mm	peso kg/m	I _x V _x cm ⁴	I _y V _y cm ⁴	I _y V _y cm ³	
HE 300 A	112,5	290	300	8,5	14	27	88,3	18263	1260	6310	421
300 B	149,5	300	300	11	19	27	117	25166	1680	8563	571
300 M	303,1	340	310	21	39	27	238	59201	3480	19403	1250
HE 320 A	124,4	310	300	9	15,5	27	97,6	22928	1480	6985	466
320 B	161,3	320	300	11,5	20,5	27	127	30823	1930	9239	616
320 M	312,0	359	309	21	40	27	245	68135	3800	19709	1280
HE 340 A	133,5	330	300	9,5	16,5	27	105	27693	1680	7436	496
340 B	170,9	340	300	12	21,5	27	134	36656	2160	9690	646
340 M	315,8	377	309	21	40	27	248	76372	4050	19711	1280
HE 360 A	142,8	350	300	10	17,5	27	112	33090	1890	7887	526
360 B	180,6	360	300	12,5	22,5	27	142	43193	2400	10141	676
360 M	318,8	395	308	21	40	27	250	84867	4300	19522	1270
HE 400 A	159,0	390	300	11	19	27	125	45069	2310	8564	571
400 B	197,8	400	300	13,5	24	27	155	57680	2880	10819	721
400 M	325,8	432	307	21	40	27	256	104119	4820	19335	1260
HE 450 A	178,0	440	300	11,5	21	27	140	63722	2900	9465	631
450 B	218,0	450	300	14	26	27	171	79887	3550	11721	781
450 M	335,4	478	307	21	40	27	263	131484	5500	19339	1260
HE 500 A	197,5	490	300	12	23	27	155	86975	3550	10367	691
500 B	238,6	500	300	14,5	28	27	187	107176	4290	12624	842
500 M	344,3	524	306	21	40	27	270	161929	6180	19155	1250
HE 550 A	211,8	540	300	12,5	24	27	166	111932	4150	10819	721
550 B	254,1	550	300	15	29	27	199	136691	4970	13077	872
550 M	354,4	572	306	21	40	27	278	197984	6920	19158	1250
HE 600 A	226,5	590	300	13	25	27	178	141208	4790	11271	751
600 B	270,0	600	300	15,5	30	27	212	171041	5700	13530	902
600 M	363,7	620	305	21	40	27	285	237447	7660	18975	1240