



TUBI SENZA SALDATURA E SALDATI

DIMENSIONI SECONDO LE NORME ANSI B 36.10 E API

diametro		spessore mm	peso del tubo liscio kg/m	identificazione		
nomi- nale pollici	ester- no mm			corri- spon- dente norme API	standard X strong XX strong	n° di sche- dula
1/8	10.3	1.73	0.375	5L	STD	40
		2.41	0.462	5L	XS	80
1/4	13.7	2.24	0.626	5L	STD	40
		3.02	0.804	5L	XS	80
3/8	17.1	2.31	0.849	5L	STD	40
		3.20	1.10	5L	XS	80
1/2	21.3	2.77	1.27	5L	STD	40
		3.73	1.62	5L	XS	80
		4.78	1.95			160
3/4	26.7	2.87	1.68	5L	STD	40
		3.91	2.19	5L	XS	80
		5.56	2.89			160
1	33.4	3.38	2.50	5L	STD	40
		4.55	3.23	5L	XS	80
		6.35	4.23			160
1¼	42.2	3.56	3.38	5L	STD	40
		4.85	4.47	5L	XS	80
		6.35	5.60			160
1½	48.3	3.68	4.05	5L	STD	40
		5.08	5.41	5L	XS	80
		7.14	7.24			160
2	60.3	3.91	5.44	5L 5LX	STD	40
		5.54	7.48	5L 5LX	XS	80
		8.74	11.11			160
		11.07	13.45	5L 5LX	XXS	
2½	73.0	5.16	8.62	5L 5LX	STD	40
		7.01	11.41	5L SLX	XS	80
		9.52	14.91			160
		14.02	20.41	5L SLX	XXS	
3	88.9	5.49	11.29	5L SLX	STD	40
		7.62	15.27	5L SLX	XS	80
		11.13	21.33			160
		15.24	27.67	5L SLX	XXS	
3½	101.6	5.74	13.57	5L SLX	STD	40
		8.08	18.63	5L SLX	XS	80
		6.02	16.07	5L SLX	STD	40
4	114.3	8.56	22.31	5L SLX	XS	80
		11.13	28.30	5L SLX		120
		13.49	33.53	5L SLX		160
		17.12	41.02	5L SLX	XXS	

diametro		spessore mm	peso del tubo liscio kg/m	identificazione		
nomi- nale pollici	ester- no mm			corri- spon- dente norme API	standard X strong XX strong	n° di sche- dula
5	141.3	6.55	21.78	5L	STD	40
		9.52	30.95	5L	XS	80
		12.70	40.28	5L		120
		15.88	49.09	5L		160
		19.05	57.42	5L	XXS	
6	168.3	7.11	28.26	5L 5LX	STD	40
		10.97	42.56	5L 5LX	XS	80
		14.27	54.20	5L 5LX		120
		18.26	67.55	5L 5LX		160
		21.95	79.18	5L	XXS	
8	219.1	6.35	33.31	5L 5LX		20
		7.04	36.79	5L 5LX		30
		8.18	42.53	5L 5LX	STD	40
		10.31	53.09			60
		12.70	64.63	5L 5LX	XS	80
10	273.0	6.35	41.77	5L 5LX		20
		7.80	51.00	5L 5LX		30
		9.27	60.29	5L 5LX	STD	40
		12.70	81.54	5L 5LX	XS	60
		15.09	95.97			80
12	323.8	18.26	114.74	5L 5LX		100
		6.35	49.72	5L 5LX		20
		8.35	65.20	5L 5LX		30
		9.52	73.82	5L 5LX	STD	
		12.70	97.44	5L 5LX	XS	
14	355.6	14.27	108.96	5L 5LX		60
		17.48	132.01	5L 5LX		80
		5.33	46.07	5L X		10
		7.92	67.94	5L 5LX		20
		9.52	81.28	5L SLX	STD	30
16	406.4	12.70	107.38	5L SLX	XS	
		15.09	126.68			60
		19.05	158.08	5L 5LX		80
		23.83	194.90			100
		6.35	62.63	5L 5LX		10
18	457.2	7.92	77.86	5L 5LX		20
		9.52	93.21	5L 5LX	STD	30
		12.70	123.29	5L 5LX	XS	40
		16.66	160.12			60
		21.44	203.48			80
18	457.2	6.35	70.59	5L 5LX		10
		7.92	87.79	5L 5LX		20
		9.52	105.14	5L 5LX	STD	
		11.13	122.36	5L 5LX		30
		12.70	139.19	5L 5LX	XS	
18	457.2	14.27	155.91	5L 5LX		40
		19.05	205.80	5L 5LX		60
		23.83	254.59	5L 5LX		80